


# CABLE FIXING ACCESSORIES

# MISCELLANEOUS ANCILLARIES


A range of adhesive and non-adhesive fixing methods for securing heating cable in position



**FT/HTP**

A self-extinguishing conformable PVC adhesive tape. Used for low temperature heaters and applications only.


Dimensions: 12mm wide x 33m roll  
Max Withstand Temp: 80 Deg C  
Min Application Temp: 0 Deg C  
Adhesive: Rubber resin



**FT/HTS**

A glass cloth based adhesive fixing tape. Used for medium temperature heaters and applications. Designed for long term performance and resistance to continuous temperature exposure.


Dimensions: 12mm wide x 50m roll  
Max Withstand Temp: 130 Deg C  
Min Application Temp: 0 Deg C  
Adhesive: Thermosetting rubber



**FT/PGL**

A non-adhesive woven glass yarn fixing tape. High tensile strength, good resistance to chemicals. Used for high temperature heaters and applications.


Dimensions: 25mm wide x 50m roll  
Max Withstand Temp: 500 Deg C (short term)  
Min Application Temp: 0 Deg C  
Adhesive: None



**FT/ALUM**

A 30 micron aluminium foil, coated one side with an acrylic, pressure sensitive adhesive. The tape is backed with a strong polythene coated release paper. Flame retardant and water resistant.


Dimensions: 75mm wide x 45m roll  
Max Withstand Temp: 110 Deg C  
Min Application Temp: 0 Deg C  
Adhesive: Acrylic



**PPS/G**


Pre-punched galvanised fixing strip, for various applications holding heating cables in position on tanks and large surface areas, etc.

Dimensions: 20mm wide x 25 metre roll  
Material: Galvanised mild steel



**FB/GT**

Stainless steel fixing bracket c/w 2 x nylon tie wraps, with several functions. Used in wide gutters to provide equal spacing for double runs of GTe heating cable. Also used to protect heating cable in difficult transition zones and supporting heating cable in drainpipes.



**FC/GT**

Metallic fixing clip with self-adhesive pad. Used for securing GTe heating cable to gutter or roof surface. (*Gutter surface must be clean and grease free.*)

Dimensions: 116mm x 18mm x 0.5mm  
Material: Alloy

**HEAT TRACE™**  
SETTING THE STANDARDS LEADING THE WAY

HANEL ul. Lagodna 11, Mala Nieszawka, 87-103 Torun 5  
tel./fax +48 56 678 71 27, mobile: +48 601 92 55 96, [www.kablegrzejne.eu](http://www.kablegrzejne.eu)

The information given herein, including drawings, illustrations and schematics (which are intended for illustration purposes only), is believed to be reliable. However, Heat Trace Ltd makes no warranties as to its accuracy or completeness and disclaims any liability in connection with its use. Users of Heat Trace Ltd products should make their own evaluation to determine the suitability of each such product for specific applications. In no way will Heat Trace Ltd be liable for any damages arising out of the misuse, resale or use of the product.