

# JUNCTION BOXES



Type	Dimensions (mm)	Entries	Terminals
WJB16	105 x 105 x 61	3 x 16mm & 2 x 20mm	6 x 4mm <sup>2</sup>

A weather proof junction box, rated at IP67, constructed from polycarbonate material. Designed for use with a glanded cable entry system.



Type	Dimensions (mm)	Entries	Terminals
WJB20	106 x 105 x 67.5	5 x 20mm	6 x 4mm <sup>2</sup>

A weather proof junction box, rated at IP67, constructed from polycarbonate material. Designed for use with a glanded cable entry system.



Type	Dimensions (mm)	Entries	Terminals
AJB1/DAJB1	106 x 105 x 67.5	4 x 20mm OR 3 x 20mm & 1 x 33mm DESTU	6 x 4mm <sup>2</sup>

A weather proof junction box, rated at IP67, constructed from anodised cast aluminium material. Designed for use with a glanded cable entry system (AJB) or with the DESTU (AJBD).




Type	Dimensions (mm)	Entries	Terminals
JB9000	120 x 120 x 75	3 x 20mm	6 x 6mm <sup>2</sup>

A weather proof junction box, rated at IP66, constructed from GRP material. Designed for use with a glanded cable entry system. Terminals may be changed to suit the application.



Type	Dimensions (mm)	Entries	Terminals
DJB9000	120 x 120 x 75	2 x 20mm & 1 x 33mm (DESTU)	6 x 6mm <sup>2</sup>

A weather proof junction box, rated at IP66, constructed from GRP material. The DJB9000 is designed for use with the DESTU (Direct Entry Sealed Termination Unit). It has a 25mm entry hole to accept the DESTU and a 20mm power cable entry gland. Additional 25mm entry is available for use with T conduit. Terminals may be changed to suit the application.



Type	Dimensions (mm)	Entries	Terminals
STRIPFREE	240 x 60 x 53	N/A	Integral

The StripFree system allows quick and simple termination and power connection of self-regulating cables without the need to strip the cable. This IP65 system has a 20 amp rating and offers considerable savings in installation time. The StripFree End Seal simply pushes on to the end of the cut cable forming a dust and weatherproof seal. StripFree Power allows 2 heating cables and 1 power supply cable. StripFree T allows for jointing of up to 3 self-regulating heating cables. Requires no special tools, no adhesives or sealing gel, no heat shrink. (See data sheet for full details.)



**HEAT TRACE™**  
SETTING THE STANDARDS LEADING THE WAY

HANEL ul. Lagodna 11, Mała Nieszawka, 87-103 Toruń 5  
tel./fax +48 56 678 71 27, mobile: +48 601 92 55 96, www.kablegrzejne.eu